



HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755  
Fax: +86-571-88926789 88132890

sales@hcforklift.com  
www.hcforklift.com



Follow us on Facebook



Follow us on YouTube



Follow us on WeChat



Download "Hangcha Forklift" App



ISO45001:2018



ISO14001:2015



ISO9001:2015



HANGCHA trucks conform to the European Safety Requirements.

2025 VERSION / COPYRIGHT 2025/01

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

# XH SERIES HIGH-VOLTAGE LITHIUM BATTERY REACHSTACKER

with capacity of 45,000kg



INNOVATIVE LITHIUM-ION



HANGCHA

The World of Hangcha

# XH SERIES HIGH-VOLTAGE LITHIUM BATTERY REACHSTACKER

The RS4531CH-XHJG electric reach stacker is a newly developed product based on Hangcha's new lithium battery platform of XH series and years of experience in R&D of internal combustion reach stacker. With the new technologies of three-phase drive motor, separate pump control, kinetic energy recovery, etc., the electric reach stacker can make quick operation response at low operation energy consumption. With intelligent and efficient performance, the vehicle is energy-saving, safe and reliable.

THE *Plus*  
FOR YOUR  
BUSINESS

VOLTAGE

**618 V**

SPEED MODELS

**3** S/P/E mode  
(Super/Power/Eco)

CHARGING TIME (20-100%)

**1.5Hour**

PROTECTION RATE

**IP67**

VEHICLE WATER RESISTANCE

**IPX4**

## Exterior

/ With the inherited exterior design of internal combustion reach stackers—pitch-down streamlined design and a smooth, vivid and sturdy profile, the vehicle has smooth coloring, a simple and elegant logo, as well as largely-curved front and rear windows, a large glass ceiling and all-glass side doors to enable a broad view.





# FASTER & MORE EFFICIENCY.

Fast charging makes it possible for the whole vehicle to work continuously, shortening the waiting time and greatly improving efficiency.

Through disruptive battery and fast charging technology, the charging time is greatly shortened.

**LI-ION**  
TECHNOLOGY

**6 YEARS**  
WARRANTY

HANGCHA provides Li-ion battery (LiFePO4) with 6 years or 12000 hours warranty.

**HIGH-VOLTAGE**

**423kWh**

Battery capacity



## Maintainability

/ An easy-to-remove hood; all the maintenance points are in easily accessible positions to facilitate repair and maintenance of electrical elements.



## Intelligence

- / High-definition LCD instruments have simple graphical interfaces to display data clearly. The interfaces can be switched to be shown in Chinese and English.
- / A vehicle central control system, which has bus architecture, and interconnected motor, battery and heat management control system.
- / Fault diagnosis and alarm functions facilitate maintenance.
- / Display: boom length, actual load, maximum load, boom height, jaw angle, outreach, load percentage bar, alarm code, etc.



## Advancement

- / A high-torque permanent magnet synchronous motor provides strong power for the vehicle with performance indicators benchmarked against that of internal combustion forklifts.
- / A 618V high-voltage platform with low system loss and a standard chilled water tank for heavy-duty truck to achieve good heat dissipation.
- / The vehicle has independently developed VCU program along with PDU+MCU+BMS+DC/DC to form a reliable and efficient drive system with flexible function configuration.
- / With motor, electric control and battery adopting liquid-cooling heat dissipation to achieve better heat dissipation, the forklift can absolutely carry out long-time and high-intensity operations.

	Type	Unit	Permanent Magnet Synchronous Motor
Drive motor	Output Power (Peak)	kW	380
	Output Torque (Peak)	N·m	4600

### Intelligent Control System

Bus meter control module	Motor control module	Spreader Control Module	Hydraulic Control Module
Lithium battery control module	Thermal Management Control Module	Remote management system	

*Functions such as single-joystick operation, spreader's vertical lifting, combined operations, throttle following, etc. make operations more efficient.*



## Safety

- / The cover of the vehicle is designed to be sealed so that the protection level of the vehicle reaches level IPX4.
- / The electrical system has high-voltage interlocking, insulation protection and monitoring, and potential balancing functions to offer vehicle-grade safety.
- / Both the battery and junction box have MSD(Manual Service Disconnect) maintenance switches to enable one-click power-down and safer maintenance.
- / Key structural parts in reference to internal combustion forklifts have been verified highly reliable by the market for many years.
- / The 6-probe visual reversing radar and wide-view cab offer a wide view without a blind corner.
- / Safety technologies such as seat sensing, dynamic antitipping protection, longitudinal dual anti-tipping protection, spreader twist-lock dual protection, startup anti-stalling protection, fault protection, etc. are used to ensure safe operations at all times.



All the motor, electronic controls and high-voltage components reach the dust and water resistance level of IP67, a high protection level adequate to withstand harsh operating environments and ensure safety and reliability.



The high-voltage lithium battery is equipped with an automatic fire extinguisher for the standard configuration. The vehicle is equipped with a pipe network automatic fire extinguisher for the standard configuration.

## Ultra-long battery life

- / Standard large-capacity lithium battery meets long battery life requirements.
- / Both the drive and operating systems are efficient vehicle-grade permanent magnet synchronization systems with low energy consumption.
- / 618V high-voltage platform, less vehicle current and minimal system heat loss
- / Braking energy and potential energy recovery effectively prolongs operating time.
- / A double-gun quick charging port offers a full charge in no more than 2 hours.



# ELME new-generation container spreader



- / For the new-generation ELME817 series telescopic container spreader, the design of the telescopic beam, turntable, etc. are optimized, so that the structural strength is increased, the weight of the spreader is 16% less than that of the spreader of the last generation and the service life is prolonged by 30%.
- / The arrangement of the oil cylinder is changed to be more conducive to maintenance.
- / Design of the hydraulic system is optimized, so that the spreader system has less pressure loss and is more energy-saving and efficient.
- / With electro-hydraulic proportional control, the speed is adjustable and the rotation angle of the spreader can be smoothly and finely controlled.
- / The latest Neuron programmable controller is used so that more optional features can be developed. Fault code information is provided according to the J1939 protocol so that fault query is quick and simple.
- / The twist-lock interlock device (mechanical and electro-hydraulic) and the real-time indication of the action indicator are provided to avoid:
  - the container is lifted when less than 4 corners are locked;
  - the twist-lock is opened when the container is lifted.
- / The lift interrupter can prevent the container from being lifted when the twist-lock is partly twisted. The lift operations can be performed only when the twist-lock is locked or unlocked.

## Efficient hydraulic system

- / American PARKER's combined hydraulic valves, PARKER's variable hydraulic pump and the load sensing hydraulic system.
- / Flexible and precise electric proportional control.
- / Light load high-speed lifting increases work efficiency. Independent temperature control and the large-size hydraulic oil cooler meet the work in the environment of up to 50 degrees.
- / Perfect high and low pressure oil filters improve the reliability of the hydraulic system.
- / Multiple hydraulic test points are set to simplify repair and maintenance work.



## Fully-suspended all-round vision cab

- / The suspended cabin, easy for maintenance.
- / With the vehicle frame damper connected and the tight sound and heat insulation design, most vibration and noise are shielded.
- / The largely-curved front and rear windows, all-glass left and right doors and large glass ceiling enable a broad view.
- / An inclinable telescopic steering column and fully-suspended adjustable seat with a high backrest and safety belt, with seat sensing and driving position sensing functions
- / A high-power cooling and heating air conditioner, two ventilation modes - internal and external circulation, sunshades, speed-adjustable wipers and defrosting function make driving more comfortable.



## Appearance and performance

- / The pitch-down streamlined design of the vehicle presents a vivid and sturdy profile.
- / The optimized counterweight contour greatly reduces the turning radius of the vehicle, broadens the side rear and front rear views, and makes driving simple and safe.
- / The left and right stair handrails, mudguard handrails, together with the anti-skid pedals and anti-skid paper, fully protect the safety of personnel.



## Stylish and comfortable

- / **Fashionable and high-end modeling elements**  
The pitch-down streamlined design presents a vivid and sturdy profile. Smooth coloring and the simple and elegant logo highlight fashionable and high-end design elements.
- / **Ergonomic control platform**  
The ergonomically-designed control platform equipped with reasonably-arranged comfortable-feel buttons enables comfortable and accurate operations, plus the adjustable steering wheel and the suspended seat with an adjustable backrest, making the operator more comfortable.
- / **Quiet, fully-suspended all-round vision cab**  
In the cab, noises are less than 78dB and there are a cooling and heating air conditioner, sunshades, a reading light, a radio and other equipment to provide a comfortable operating environment.



## Features

	Standard	Options
<b>Transmission</b>		
Pneumatic tyre	●	
Solid tyre		○
<b>Steering system</b>		
Fully hydraulic power steering	●	
Centralized lubrication system (machine)		○
<b>Truck</b>		
Tow pin	●	
Electrostatic discharge chain		○
Rear-view mirror on right & left mudguards	●	
<b>Operating system</b>		
Integrated joystick	●	
Adjustable steering column	●	
Adjustable armrest	●	
<b>Hydraulic system</b>		
Variable hydraulic pump system	●	
Operation proportion control	●	
Higher lifting speed at light load	●	
<b>Cab</b>		
Cabin	●	
Climate control system (air-conditioning and heater)	●	
Radio	●	
Sunshade	●	
USB charging interface	●	
Clothes hanger hook	●	
Reading light	●	
1 x 24V power supply		○
1 x 12V power supply		○
License plate frame		○
Fan	●	
<b>Lifting components</b>		
Standard lifting height	●	
Spreader & twistlock double protection	●	
Emergency descent	●	
Twistlock counter	●	
Spreader swing prevention	●	
4 x Spreader twistlock camera		○
2 x Spreader twistlock light	●	
<b>Other</b>		
Standard color	●	
User defined colour		○
Fire extinguisher (2kg/4kg)		○
Vehicle toolkit	●	
Heating pack for the cold region		○
Movable Cabin	●	
Overload protection	●	
Lifting height indicator on display	●	
Dynamic speed Limit depending of lift height( customer defined)		○
Automatic throttle control (lift / tilt / spreader)	●	

	Standard	Options
<b>Electrical System</b>		
Operator Presense System (OPS) with buzzer	●	
LCD display screen	●	
Main power switch	●	
Emergency power off switch	●	
Maintenance-free 24V lead acid battery	●	
Reverse buzzer	●	
High decible horn	●	
LED lights (entire vehicle)	●	
4 x Working light on front mudguard	●	
4 x Working light on boom	●	
2 x Rear working light	●	
Reverse sensor	●	
Rearview camera system	●	
Rearview camera system with memory		○
Front & rearview camera system		○
Front & rearview camera system with memory		○
4 directions camera system with single display		○
4 directions camera recording system with single display		○
In cabin CCTV		○
Rear blue safety light		○
Front and rear blue safety light		○
Three sided blue danger zone light		○
Overspeed alarm		○
Speed limitation		○
Voice reverse alarm		○
Automatic fire suppression system	●	
Two-way radio		○
Weight indicator in display	●	
Flashing warning light (non rotating) with control switch	●	
Eccentric load weighing (with printer)		○
Tyre pressure monitoring		○
On-board diagnostics system	●	
Water cooling system for lithium battery	●	
Automatic fire suppression system for lithium battery pack	●	
Manual Service Disconnect (MSD) switch	●	
High voltage interlock	●	
Insulation protection	●	
Power-on self-test	●	
Energy recovery (braking regeneration)	●	
Energy recovery (descent regeneration)	●	
Vehicle Control Unit (VCU)	●	
Dual charging ports	●	
Override switch	●	
central control panel for lighting system	●	
Torque limitation	●	
Vertical lift control		○
Turning deceleration		○
Hour meter	●	
Battery charge indicator	●	
Low hydraulic pressure alarm indicator	●	
Hydraulic oil filter warning indicator	●	
Drive mode indicator	●	
Parking brake indicator	●	
Service indicator	●	

# XH Series High-voltage Lithium Battery Reachstacker Specification

Distinguishing mark	1.1	Manufacturer	HANGCHA GROUP CO.,LTD.		
	1.2	Model designation	RS4531CH-XHJ6		
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas	Electric		
	1.4	Operator type: hand, pedestrian, standing, seated, order-picker	Rider seated		
	1.5	Rated capacity/rated load(L1,L2,L3)	Q (kg)	45000/31000/16000	
	1.6	Load centre,from front face of types, row 1	c (mm)	1965	
		Load centre,from front face of types, row 2	c (mm)	3815	
		Load centre,from front face of types, row 3	c (mm)	6315	
		Stacking capacity,in container row 1-2-3 of 8'6"/9'6"		5/5-5/4-4/3	
	1.8	Lost load centre,to front face of tyres	x (mm)	840	
1.9	Wheelbase	y (mm)	6000		
Weight	2.1	Service Weight	kg	72600	
	2.2	Axle load,front at load centre L1,unloaded-loaded	kg	33600/99600	
		Axle load,front at load centre L2,unloaded-loaded	kg	34200/93600	
	2.3	Axle load,rear at load centre L1,unloaded-loaded	kg	39000/18000	
		Axle load,rear at load centre L2,unloaded-loaded	kg	38400/10000	
Wheels & tyres	3.1	Tyres: solid rubber, superelastic, pneumatic, polyurethane	Pneumatic		
	3.2	Tyre size, front	18.00-25-40pr		
	3.3	Tyre size, rear	18.00-25-40pr		
	3.5	Wheels, number front / rear (x = driven wheels)	4x/2		
	3.6	Tread, front	b10 (mm)	3050	
	3.7	Tread, rear	b11 (mm)	2790	
	Dimensions	4.1	Telescopic boom lift angle,Raised/lowered	$\alpha/\beta(^{\circ})$	60/0
4.2		Height telescopic boom lowered	h (mm)	4700	
4.4		Lift (L1,L2,L3)	h2 (mm)	15120/13600/10700	
		Seat height relating to SIP	h3 (mm)	2615	
4.15		Twistlock height lowered	h13 (mm)	1280	
4.19		Overall length with boom	l1 (mm)	11625	
4.20		Overall length	l2 (mm)	8123	
4.21		Truck width over drive axle	b1 (mm)	4220	
		Spreader sideshift	mm	+/-800(1600)	
		Spreader rotation	deg	+105/-195	
4.31		Ground clearance minimum	m1 (mm)	400	
4.33		Stacking aisle 20' container	Ast (mm)	11350	
4.34		Stacking aisle 40' container	Ast (mm)	13650	
4.35		Turning radius	Wa (mm)	8100	
Performance data		5.1	Travel speed, laden/unladen	km/h	20/22
	5.2	Lift speed, laden/unladen	m/s	0.250/0.420	
	5.3	Lowering speed, laden/unladen	m/s	0.360/0.360	
	5.6	Drawbar pull, laden/unladen	N	230000	
	5.8	Gradeability, laden/unladen	%	20/20	
	5.10	Service brake		Wet disc	
	Electric drivetrain	6.1	Drive motor rating S9 Rated/Peak	kW	214/380
		6.2	Lift motor rating at S9 Rated/Peak	kW	180/260
6.4		Battery Capacity	kWh / Ah	423/684	
		Nominal Voltage	V	618	
Addition data	10.1	Operating pressure for attachments	Mpa	19	
	10.3	Hydraulic Tank - capacity (drain & refill)	liter	600	
	10.7	Sound pressure level at the driver 's seat	dB (A)	67	
	10.8	Towing coupling,type DIN 15170	mm	$\phi$ 50	

